


2178–L/S Series Fiber Optic Splice Cases and Accessories



The 3M[™] 2178 Fiber Optic Splice Case family has always given you great protection for fiber optic connections. Now, the addition of 3M[™] 2178-L/S Series Fiber Optic Splice Cases adds more capabilities to the family.

More chemical-resistant

With the new addition you get all the features of the popular 2178 splice case. Plus, the 2178-L/S series consists of a tough chemical-resistant material and a new gasket seal that make this the ideal splice case for outside plant, underground, aerial, pedestal and direct buried applications.

Meets your changing network needs

The 2178-L/S series is designed with larger and smaller interchangeable closure halves so you can select the size case that meets your needs today, but with the flexibility to expand for the future. Cable ports and space for trays can be added at reentry with the 3M™ 2181-L/S Cable Addition Kit.


The ease of installation is unsurpassed, requiring no special tools or complicated training procedures. The closures are easily reenterable to allow access to the splices.

The ultimate protection for fiber optic connections

The 2178-L/S series feature a tough, rigid non-filled case, tested under real-world conditions, that stands up to even the most severe conditions of moisture, vibration and extreme temperatures. The closure will withstand up to 200 pounds (90.7 kg) compression.

Design improvements to the 2178-L/S series include changes to improve the cable strain relief and a movable tray support. The closures hold cables of varying sizes and provide flexibility to add ports on both ends with the cable addition kit. The 2178-L/S series splice cases can be used with the 3M[™] 2522 or 2523 Small Fiber Splice Organizer Trays or the 3M[™] 2524 Fibrlok[™] Small Fiber Splice Organizer Tray and most other commercially available trays..

Features	Benefits	
2178-L/S Series FiberOptic Splice Cases		
Constructed of a highly chemical-resistant material	Use in buried applications	
Gasket seal	Easy reentry and reusable seal	
Unique strength member clamp assembly	Prevents cable sheath movement with temperature changes	
Several sizes with interchangeable parts	Expandable system to fit capacity and space requirements	
Multiple cable entry options	Butt or in-line configuration for splicing	
No special tools required	Easy installation and reentry	
Non-filled closure	No compound required; easier reentry	
Multiple ground studs	Isolated grounding capability	
Pressurization Valve	Provides ability to flash test	
Varying cable port sizes	Accommodates all common trunk and feeder cable sizes	
Expandable from two cable entries per end up to six	Add cable with minimum disturbance; eliminates splice rebuilding when adding lines	
3M™ 2522 and 2523 FiberOptic Splice OrganizerTrays	****	
Meets Bellcore requirement for bend diameter	Easy maintenance	
Trays allow entry and exit of buffer tubing at any of the four corners	Provides flexibility in fiber management	
Extra tray depth	Ribbon fiber may be coiled without twisting	
Modular design of the splice holder	Accommodates many types of splices	
Stackable hinged tray	Easy access without removing other trays	
3M™ Fibrlok™ 2524 FiberOptic Splice OrganizerTray		
Single entry point	Controls fiber management	
Hinged trays snap together	Stackable; individual tray access	
Flame retardant / isopropyl alcohol resistant	Meets fire codes and industry standards	
4-inch (10.16 cm) bend diameter	Individual fiber access; allows easy maintenance	



3M[~] 2178-S case mounted on strand,



2178-S




2178-LS




2178-LL

2178-S FiberOptic Splice Case




Dimensions Shown: Inches (Centimeters)

2178-LS FiberOptic Splice Case




Dimensions Shown: Inches (Centimeters)

2178-LLFiberOptic Splice Case



Dimensions Shown: Inches (Centimeters)



2181-LSCable Addition Kit (Gasket is factory installed.)


MULTIPLE SOLUTIONS (CONTINUED)

4 Flexible Environmental Applications


The 3M[™] Fiber Optic Splice Closure 2178 family can be effectively used in nearly any application including aerial (pole and strand) mount, central office vault, manhole, pedestal and handhole. It can also accommodate most splicing methods (mechanical and fusion) as well as inline and butt splicing configurations.

6 Network Flexibility

3M designs a variety of sizes, materials (flame retardant vs. non flame retardant) and configuration options so that our fiber optic splice closures can be used in almost every segment of the network. A single product family meets a range of needs.



3M~ Fiber Optic Splice Closure 2178/FR Flame Retardant Series



2178-L/S Series Max	cimum Splic	e Capacities with 3	M ⁻ Splice	Organizer Trays	
Product Number	Fibrlok™	Fibrlok [™] Multi-fiber	Fusion	Ribbon Fusion	Comments
2178-S w/2 2522	24	16 (192 fibers)	48	20 (240 fibers)	
2178-S w/2 2523	48	24 (288 fibers)	96	24 (288 fibers)	
2178-S w/2 2524	48				
2178-S w/2 2524-A			48	8 (96 fibers)	
2178-S w/2 2524-FT			48		
2178-S w/2 2524-MF	4	6 (72 fibers)			
2178-S w/4 2522	48	32 (384 fibers)	96	40 (480 fibers)	One 2181 cable addition kit
2178-S w/4 2523	96	48 (576 fibers)	192	48 (576 fibers)	One 2181 cable addition kit
2178-S w/4 2524	96				One 2181 cable addition kit
2178-S w/4 2524-A			96	16 (192 fibers)	One 2181 cable addition kit
2178-S w/4 2524-FT			96		One 2181 cable addition kit
2178-S w/4 2524-MF	8	12 (144 fibers)			One 2181 cable addition kit
2178-LS w/5 2522	60	40 (480 fibers)	120	50 (600 fibers)	
2178-LS w/5 2523	120	60 (720 fibers)	240	60 (720 fibers)	
2178-LS w/7 2524	168				
2178-LS w/7 2524-A			168	28 (336 fibers)	
2178-LS w/7 2524-FT			168		
2178-LS w/7 2524-MF	14	21 (252 fibers)			
2178-LS w/8 2522	96	64 (768 fibers)	192	80 (960 fibers)	One 2181 cable addition kit
2178-LS w/8 2523	192	96 (1152 fibers)	384	96 (1152 fibers)	One 2181 cable addition kit
2178-LS w/10 2524	240				One 2181 cable addition kit
2178-LS w/10 2524-A			240	40 (480 fibers)	One 2181 cable addition kit
2178-LS w/10 2524-FT			240		One 2181 cable addition kit
2178-LS w/10 2524-MF	20	30 (360 fibers)			One 2181 cable addition kit
2178-LS w/10 2522	120	80 (960 fibers)	240	100 (1200 fibers)	Two 2181 cable addition kits
2178-LS w/10 2523	240	120 (1440 fibers)	480	120 (1440 fibers)	Two 2181 cable addition kits
2178-LS w/13 2524	312				Two 2181 cable addition kits
2178-LS w/13 2524-A			312	52 (624 fibers)	Two 2181 cable addition kits
2178-LS w/13 2524-FT			312		Two 2181 cable addition kits
2178-LS w/13 2524-MF	26	39 (468 fibers)			Two 2181 cable addition kits

NOTE: 2178-LLhas the same splice capacity as 2178-LS with additional space for buffer storage. Capacity may be affected by the cable size and number of cables installed. Please call Customer Service for more information.

2522 Small Tray	12	8 (96 fibers)	24	10 (120 fibers)	
2523 Large Tray	24	12 (144 fibers)	48	12 (144 fibers)	
2524 Tray	24				
2524-ATray			24	4 (48 fibers)	
2524-FTTray			24		
2524-MF Tray	2	3 (36 fibers)			

3M[™] Splice Cases and Accessories Ordering Information

2524 Splice Organizer Tray Holds 24 Fibrlok splices and eight buffer tubes


Dankaring	Min Ordon
Packaging	Min. Order
i kives.	reacri
1 kit/cs.	1 each
1 kit/cs.	1 each
1 kit/cs.	1 each
Packaging	Min. Order
100/cs.	100 each
5/cs.	5 each
10/cs	10 each
1/cs.	1 each
1 kit/cs.	1 each
1 kit/cs.	1 each
100/cs.	100 each
10 kits/cs.	10 kits
10 kits/cs.	10 kits
50/cs.	50 each
2/pkg,12pkg/cs.	12 pkgs.
2/pkg,12pkg/cs.	12 pkgs.
2/pkg,12pkg/cs.	12 pkgs
	12 pkgs.
2/pkg,12pkg/cs.	12 pkgs.
2/pkg,12pkg/cs.	3 each
	1 kit/cs. 1 kit/cs. 1 kit/cs. 1 kit/cs. 1 kit/cs. Packaging 100/cs. 5/cs. 10/cs. 1/cs. 1/cs. 1/cs. 1 kit/cs. 1 kit/cs. 1 kit/cs. 10/cs. 2/pkg,12pkg/cs. 2/pkg,12pkg/cs.

3/cs.


3 each

3M™ Splice Case Accessories Ordering Information, continued


2524-ASplice Organizer Tray Holds four mass fusion or 24 single fusion splices, or a combination of 20 single fusion and four mass fusion	3/cs.	3 each	
2524-FTFusion Splice Organizer Tray Holds 24 single fusion splices	3/cs.	3 each	
2524-MF Fibrlok Multi-fiber Splice Organizer Tray Holds three Fibrlok Multi-fiber and four single Fibrloks	3/cs.	3 each	
2524-F Fusion Splice Insert Adapts the 2524 Tray for fusion splices	24/cs.	24 each	
2526 Strap Kit for Organizer Trays Holds 2522 and 2523 Trays in place in closure	24 kits/cs.	24 kits	



3M[™] 2522 Fiber Optic Splice Organizer Tray with cover



3M[™] 2523 Fiber Optic Splice Organizer Tray with cover



3M[™] 2524 Fiber Optic Splice Organizer Tray with cover

*STis a registered trademark of Lucent.

Important Notice

All statements, technical information, and recommendations related to Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of Seller. The statements contained herein are made in lieu of

all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS THAT WERE DEFECTIVE.



Telecom Systems Division

6801 River Place Blvd. Austin, TX 78726-9000 800/426 8688 FAX 800/626 0326 http://www.mmm.com/telecom



Recycled paper 40% pre-consumer 10% post-consumer

Printed in USA. © 3M 1997 80-6109-3465-7