

PEDESTRIAN THERMAL SENSOR

SPECIFICATIONS

| POWER INPUT | 12 to 42V DC | | |
|-----------------------------------|--|----------------------------------|--------------------|
| POWER CONSUMPTION | 3 watts | | |
| | LENS TYPE | FIELD OF VIEW | DETECTION DISTANCE |
| SENSOR OPTIONS | 95° | Horizontal: 95° Vertical: 69° | 0 to 40 feet |
| | 56° | Horizontal: 56° Vertical: 45° | 33 to 82 feet |
| DETECTION ZONES | Up to 8 | | |
| INSTALLATION HEIGHT | 11.5 to 26 feet; dependent on number of zones to monitor and location of sensor | | |
| THERMAL SENSOR DETECTOR TYPE | Long Wave Infrared (8 to 14 um) | | |
| CONFIGURATION | Ethernet, Wifi | | |
| HOUSING | Aluminum with sunshield | | |
| BRACKET | Aluminum, horizontal or vertically fixed with banding straps | | |
| ENCLOSURE | IP-67 rated | | |
| MATERIALS | All weatherproof UV-resistant | | |
| SHOCK & VIBRATION | NEMA TS2 | | |
| FCC | FCC part 15 class A | | |
| OPERATING TEMPERATURE RANGE | -40°F to 131°F (-40°C to 55°C) | | |
| DIMENSIONS (INCLUDING BRACKET) | Horizontally mounted: 8.3"W x 10.8"H x 2.0"D Vertically mounted: 6.4"W x 12.7"H x 2.2"D | | |

