

# Milwaukee Harp Lights

For municipal/residential applications, TAPCO offers the Single Harp Light models in three sizes. These traditional, time-tested fixtures can be mounted on a variety of pole types, including aluminum and concrete. The aluminum reflector and polycarbonate globe provide symmetric light dispersal for an even, warm glow. The canopy over the globe helps reduce unwanted up-lighting. All TAPCO Harp fixtures are constructed of sturdy sand-cast aluminum. Custom colors are also available.

- Your lamp choices include incandescent, high pressure sodium, LED, Fluorescent and Metal Halide
- Door-mounted photocell provides a light-sensitive switch for efficient energy use
- Complete turnkey kits available
- Unique historic look







MH100



MH200



MH500

## MH100 Milwaukee Harp light

Attaches to 4" outer diameter poles

- Superior performance
- Ease of maintenance
- Aluminum reflector
- Polycarbonate globe

### Optimal mount height:

- 9'–10' aluminum poles
- 10'–15' concrete poles

### Optimal spacing:

- 50'–100' apart

MH100, 25w LED bulb, 120VAC, capital, door-mount photocell, black 203-100525121421

MH100, 70w High Pressure Sodium bulb, ballast, 120VAC, capital, door-mount photocell, black 203-100470121421

MH100, incandescent bulb, 120VAC, capital, door-mount photocell, black 203-100100121421

## MH200 Milwaukee Harp light

Attach to 3" outer diameter poles

- Superior performance
- Ease of maintenance
- Aluminum reflector
- Polycarbonate globe

### Optimal mount height:

- 8'–10' above ground

### Optimal spacing:

- 25'–40' apart

MH200, 25w LED bulb, 120VAC, capital, door-mount photocell, black 203-200525122321

MH200, 50w High Pressure Sodium bulb, ballast, 120VAC, capital, door-mount photocell, black 203-200470122321

MH200, incandescent bulb, 120VAC, capital, door-mount photocell, black 203-200450122311

## MH500 Milwaukee Harp light

Attaches to 3" outer diameter poles

- Superior performance
- Ease of maintenance
- Aluminum reflector
- Polycarbonate globe

### Optimal mount height:

5 ½'– 6 ½' above ground

### Optimal spacing:

15' – 25' apart

MH500, 18w LED bulb, 120VAC, capital, door-mount photocell, black 203-500518125321

MH500, 35w High Pressure Sodium bulb, pole-mount ballast, 120VAC, capital, door-mount photocell, black 203-500435125311

MH500, incandescent bulb, 120VAC, capital, door-mount photocell, black 203-500100125321

## LED bulbs

For retrofitting TAPCO MH series Harp Lights or other luminaires in the field



- 2.83"W x 9.65"L (72 mm x 245 mm)
- Actual lamp output: 2,400 lm
- Voltages: 85-245 volt AC, or 12v DC
- Emission color: warm white: 3,000 to 5,000K, cool white: 5,000 to 7,000K
- Working temperatures: - 30 to 45°C
- Working lifespan: >30,000 hours
- Many other options available



25 watt LED bulb, 2,200 lumen 106977

40 watt LED bulb, 3,000 lumen 110247



1-800-236-0112 • [www.tapconet.com](http://www.tapconet.com)

